

D713

Desk Phone



Key Features

- 2.8" (320x240) Color LCD
- 4 configurable self-labeling multicolor LED keys
- Wideband audio
- Elegant design
- 2-port Gigabit Ethernet switch (RJ45)
- Electronic Hook Switch (EHS)¹ support for wireless headsets
- 3-year standard warranty



Power over Ethernet



IPv6 & IPv4



Headset Compatible



Security (TLS & SRTP)



HD Audio



Gigabit Ethernet



On-Screen Labels

Phone Features

- 6 SIP identities / accounts
- XML browser
- Call lists for dialed, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP PBX platforms
- Speed dialing
- URL dialing
- Local dial plan
- Automatic redial on busy
- Call completion (busy / unreachable)(2)
- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold
- Music on hold(2)
- Blind and attended transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup(2)
- Call park, call unpark(2)
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock
- Client matter code (CMC)(2)
- Unified Communications ready

Audio/Codecs

- G.711 A-law, u-law
- G.722 (wideband)
- G.726, G.729ab, GSM 6.10 (FR)
- Built-in assignable ringtones
- Comfort noise generator (CNG)
- Voice activity detection (VAD)

Setup

- Configurable through web interface
- Provisioning:
 - Automatic loading of settings via HTTP / HTTPS / TFTP
 - DHCP Options 66/67
 - Snom Redirection Service
 - Remote management via TR-069 / TR-111

Protocols

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

User Interface

- Localization (language, time, dial tone)
- Red LED for call indication / message waiting
- 4 context sensitive keys
- 4 programmable line / function keys with multicolor LEDs
- Dedicated keys for: Message, DND, directory, menu, transfer, hold, page
- Mute, speakerphone, headset keys
- Volume key
- 5-way navigation key
- OK and cancel keys
- Sensor-assisted user interface

Security

- 802.1X Authentication and EAPOL
- Transport layer security (TLS)
- SRTP (RFC3711), SIPS, RTCP
- HTTPS server / client
- Password-protected web interface
- VPN support
- VLAN (IEEE 802.1Q)
- LLDP-MED, RTCP-XR

Specifications, Weight & Dimensions

- Dimensions (approx.): 7.28" x 3.54" x 8.66"
- With desk stand: 7.28" x 8.46" x 6.81"
- Weight (approx.): 1.8 lbs
- Input voltage: 5V DC (SELV)
- Power supply: PoE or 5Vdc power adapter¹, 10 Watts
- Handset: 4P4C
- Headset: 4P4C; Support for Snom EHS Advanced¹
- Hearing aid compatible (HAC) handset
- Environmental conditions:
 - Ambient temperature: 0°C to 35°C (32°F to 95°F)
 - Storage temperature: -10°C to 45°C (14°F to 113°F)
- Humidity: 5% to 95% (non-condensing)
- Included in delivery:
 - Phone unit
 - Foot stand
 - Handset with cord
 - Ethernet cable
 - Quick Start Guide
- Color: Black
- Warranty: 3 years
- Part Number: 00004592
- APN: 80-S157-00

APN # for Optional Accessories

- Power Adaptor Snom A6 / US Clip: 26-350200-3UL
- Snom EHS Advanced: 89-S015-00
- Wallmount Plate for D7 Series: 89-S013-00
- A100D Binaural Headset: 89-S020-00
- A100M Mono Headset: 89-S019-00

- 1 - Optional accessory
- 2 - If supported by PBX